TOPEAGLE®

产品推荐
Product recommendation

直驱筒式多针系列

TMN-4412P-UTC-D-AT

Cylinder-bed multi-needles sewing machine with direct drive motor

PL:贴条装置 Attaching line system
MD:前拖轮 Metering device
RT:松紧张力器 Elastic band' s tensioner



TMN-4412P-UTC-D-AT

机种Model:
筒式多针机
Cylinder-bed multi-needles sewing machine with direct

机针数 Quantity of needles
4-25针
4-25 needles

后拖轮 With back puller
平轮 Smooth puller
齿轮 Teeth puller

气动剪线
Automatic air cut+air catch system

直驱伺服马达
Direct drive serve motor

气动抬压脚装置
Air foot lift System

4针/6针/8针/12针/13针筒式多针机

4needle/6needle/8needle/12needle/13 needle cylinder-bed multi-needle sewing machine

TMN-4404PMD-D
TMN-4406PMD-D
TMN-4408PMD-D
TMN-4412PMD-D
TMN-4413PMD-D



适用于各种服装的上松紧、滚条等。自动切线装置、气动开闭卷边器及自动切线等分型号，附属装置可供利用。筒形外周长420mm，童装及上环状松紧变得很容易操作。

Application: attaching elastic and line tape to sweat pants, pajamas, trunks and similar garments. Major features of this series are wide range of available gauge sizes(4-13 needles), cylinder bed (420mm in circumfence), elastic guide roller and our unique rear puller mechanism. These features make this series popular for attaching preclosed elastic. Automatic thread cutter(UTC) increases productivity by trimming thread accurately and leaving less thread. which chrtail production cost.



4针/6针/12针/13针筒式自动剪线多针机

4needle/6needle/12needle/13 needle cylinder-bed multi-needle sewing machine with auto trimmer

TMN-4404P-RT-UTC-D 1X4N
TMN-4406P-RT-UTC-D 1/4X6N
TMN-4412P-RT-UTC-D 1/4X12N
TMN-4413P-RT-UTC-D 自由针位





19针/25针筒式多针机

19needle/25needle cylinder-bed multi-needle sewing machine

TMN-4419P-D 1/4X19N
TMN-4425P-D 3/16X25N

第一根针到最后一根针可达到 11.5cm的距离
The distance from first needle to last needle is 11.5cm.



TMN-4404P-RT-UTC-D	UOX113 14	4	8	1/4,1/3	1.8-4.5	8	4500	50/46	0.20
TMN-4406P-RT-UTC-D	UOX113 14	6	12	1/4	1.8-4.5	8	4500	51/47	0.20
TMN-4412P-RT-UTC-D	UOX113 14	12	24	1/4,3/16	1.8-4.5	8	4500	50/46	0.20
TMN-4413P-RT-UTC-D	UOX113 14	13	26	1/4,1/8,1/8,1/4,1/4,1/8,1/8,1/4,1/4,1/8,1/8,1/4,	1.8-4.5	8	4500	50/46	0.20
TMN-4404PMD	UOX113 14	4	8	1/4,1/3,3/8,5/16	1.8-4.5	8	4500	51/47	0.20
TMN-4406P	UOX113 14	6	12	1/4,5/16,3/8	1.8-4.5	8	4500	51/47	0.20
TMN-4406PL	UOX113 14	6	12	1/4,5/16,3/8	1.8-4.5	8	4500	52/48	0.20
TMN-4408P	UOX113 14	8	16	1/4,5/16,3/8	1.8-4.5	8	4500	51/47	0.20
TMN-4408PL	UOX113 14	8	16	1/4,5/16,3/8	1.8-4.5	8	4000	52/48	0.20
TMN-4412P	UOX113 14	12	24	1/8,3/16,1/4	1.8-4.5	8	4000	52/48	0.20
TMN-4411PXP	UOX113 14	4	8	1/8-1/8-1/8-1/8-1/4-1/4-1/8-1/8-1/8-1/8	1.8-4.5	8	4000	52/48	0.20
TMN-4413P	UOX113 14	13	26	1/4-1/8-1/8-1/4-1/4-1/8-1/8-1/4-1/4-1/8-1/8-1/4	1.8-4.5	8	4000	51/47	0.20
TMN-4413PXP	UOX113 14	4	8	1/4-1/8-1/8-1/4-1/4-1/8-1/8-1/4-1/4-1/8-1/8-1/4	1.8-4.5	8	3000	56/52	0.25
TMN-4419P	UOX113 14	19	38	1/4	1.8-4.5	8	2500	56/52	0.25
TMN-4425P	UOX113 14	25	50	3/16	1.8-4.5	8	2500	56/52	0.25